

200W High bay Lighting specification

Features:

- •Superior color rendition index >80
- •40,000hrs life of LEDs
- Aluminum body parabolic reflector.
- •High efficacy of 105lm/W
- •1.2M flex and plug.
- Low power consumption
- Instant on/off operation
- Mercury free, lead free
- Temperature compensation technology for longer life
- · One man installation
- Replaces up to 400W HID fittings
- Optional glass retention for food applications
- 5 year full performance warranty






Brightness Contrast View Angle

H200 LUX Information

Distance	ActualLux	160°	DIm (m)
4M	371 Lux		9 m
6M	305Lux		14m



Save \$315/Yrs Comparison Vs 450W Mercury

	YEAR COST	LIFE SPAN	WARRANTY	TEMPUATURE	GREENHOUSE GASES
450W W V high bay	\$567	10,000HRS	NO WARRANTY	300°	22.5TONES
200W Lumen power	\$252	40,000HRS	5 YEAR	50°	10 TONES

Based on current cost of electricity used at \$0.29KW/Hrs, running 12 hours per day,



Specification

Model	High bay Light	
Wattage	200w	
Lumen	21,000LM	
Light source	AC COB	
Input Voltage	AC240V (Dimmable option)	
CRI	>Ra82	
PF	>0.55	
CCT	5000K	
Beam angle	160 degree	
Lamp housing	Aluminum	
Lamp size	Dia395*100mm,	
Operation Temp	-20-60℃	
Lifetime	40000hrs	
Certification	SAA 150445	